



- Shorter stroke bellows cups give faster response versus traditional bellows design
- Large thin sealing lip gives better contact for corrugated and textured surfaces
- 10mm to 50mm diameters
- Multiple mounting options give the system designer unlimited flexibility
- Available in long wearing Nitrile (NBR) and high temperature Silicone (SIT)

### **PBH Series side barbed adapters**

Cups can be secured with a bolt thru a plate or "L" bracket and allow the vacuum connection from the side.



### **PBV Series barbed bulkhead adapters**

Cups can be mounted with jam nuts and allow a vacuum connection from the top.



## Applications

Versatile bellows cup design provides increased sealing lip and level compensation for products with irregular, textured, curved surfaces or flexible sheets. Good for corrugated and smooth surfaces.

### **PBHS Series level compensators with side barbed adapters**

Spring loaded to allow a cushioned pick up and also adjusts to different levels. Side vacuum connections.



### **PBVS Series level compensators with top barbed adapters**


Spring loaded cups with top vacuum connections




## Replacement cups

■ External dimensions


● PB-10




● PB-15




● PB-20




● PB-30



● PB-40



● PB-50



Cup Diameter	Nitrile (NBR)	Silicone (SIT)
10	PB.10.NBR	PB.10.SIT
15	PB.15.NBR	PB.15.SIT
20	PB.20.NBR	PB.20.SIT
30	PB.30.NBR	PB.30.SIT
40	PB.40.NBR	PB.40.SIT
50	PB.50.NBR	PB.50.SIT